

Datasheet

PERFECTCLIME® Modelle

TERM2000 IP67



Code	Wattage	Material Color	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Features	Cable	Connection	Heatable area m ²	Spare tube	Mounting
UPCRCA165V2	1,65 kW	Alu polished	4260051484426	67	70 x 9,5 x 12,5	2900	1, 2, 4	1,9m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	13-14	ULG1650V	Wall & ceiling
UPCRCA200V2	2,0 kW	Alu polished	4260051484488	67	70 x 9,5 x 12,5	2900	1, 2, 4	1,9m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	ULG2001V	Wall & ceiling
UPCRCAC165V29010	1,65 kW	White	4260409691674	67	70 x 9,5 x 12,5	2900	1, 2, 4	1,9m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	13-14	ULG1650V	Wall & ceiling
UPCRCAC200V29010	2,0 kW	White	4260409691681	67	70 x 9,5 x 12,5	2900	1, 2, 4	1,9m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	ULG2001V	Wall & ceiling
UPCRCAC165V29005	1,65 kW	Black	4260409691698	67	70 x 9,5 x 12,5	2900	1, 2, 4	1,9m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	13-14	ULG1650V	Wall & ceiling
UPCRCAC200V29005	2,0 kW	Black	4260409691704	67	70 x 9,5 x 12,5	2900	1, 2, 4	1,9m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	ULG2001V	Wall & ceiling

UPCRCAC165V27016	1,65 kW	Anthracite	4260409691711	67	70 x 9,5 x 12,5	2900	1, 2, 4	1,9m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	13-14	ULG1650V	Wall & ceiling
UPCRCAC200V27016	2,0 kW	Anthracite	4260409691728	67	70 x 9,5 x 12,5	2900	1, 2, 4	1,9m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	ULG2001V	Wall & ceiling

TERM2000 L&H IP65



Code	Wattage	Material Color	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Features	Cable	Connection	Heatable area m ²	Spare tube	Mounting
UPCRLH17652	1,65 kW + 7 Watt	Alu polished	4260051484556	65	91 x 9,5 x 12,5	4050	1,2,4,5	1,9m 5-wire 1,5mm ² , Wire-end sleeves	2/N/PE ~ 230 V 50 Hz	13-14	ULG1650V	Wall & ceiling
UPCRLH21652	2,0 kW + 7 Watt	Alu polished	4260051484570	65	91 x 9,5 x 12,5	4050	1,2,4,5	1,9m 5-wire 1,5mm ² , Wire-end sleeves	2/N/PE ~ 230 V 50 Hz	14-16	ULG2001V	Wall & ceiling
UPCRLH1765F2	1,65 kW + 7 Watt	Alu polished	4260051484563	65	87 x 9,5 x 12,5	4050	1, 2, 4, 5	1,9m 5-wire 1,5mm ² , Wire-end sleeves	2/N/PE ~ 230 V 50 Hz	13-14	ULG1650V	Wall & ceiling
UPCRLH2165F2	2,0 kW + 7 Watt	Alu polished	4260051484594	65	87 x 9,5 x 12,5	4050	1, 2, 4, 5	1,9m 5-wire 1,5mm ² , Wire-	2/N/PE ~ 230 V 50 Hz	14-16	ULG2001V	Wall & ceiling

								end sleeves				
UPCRLH42652	2 x 2,0kW + 14W	Alu polished	4260051484624	65	200 x 9,5 x 12,5	7100	1, 2, 4, 5	2m 5-wire 2,5mm ² , Wire-end sleeves	3/N/PE ~ 235 V 50 Hz	28-30	ULG2001V	Wall & ceiling

TERM TOWER PALMS IP67



Code	Wattage	Material Color	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Features	Cable	Connection	Heatable area m ²	Spare tube	Mounting
UPCRTT400V	2 x 2,0 kW	Alu polished	4260051484631	67	110 x 250-270	4900	1, 2, 4	10m 5-wire 2,5mm ² , Wire-end sleeves	3/N/PE ~ 400 (3N) V 50 Hz	26-28	ULG2001V	Floor
UPCRTT600V	3 x 2,0 kW	Alu polished	4260051484648	67	110 x 250-270	5100	1, 2, 4	10m 5-wire 2,5mm ² , Wire-end sleeves	3/N/PE ~ 400 (3N) V 50 Hz	36-37	ULG2001V	Floor
UPCRTT800V	4 x 2,0 kW	Alu polished	4260051484365	67	110 x 250-270	5270	1, 2, 4	10m 5-wire 2,5mm ² , Wire-end sleeves	3/N/PE ~ 400 (3N) V 50 Hz	50-51	ULG2001V	Floor

UPCRTTC400V9005	2 x 2,0 kW	Black	4260409691797	67	110 x 250–270	4900	1, 2, 4	10m 5-wire 2,5mm ² , Wire- end sleeves	3/N/PE ~ 400 (3N) V 50 Hz	26-28	ULG2001V	Floor
UPCRTTC600V9005	3 x 2,0 kW	Black	4260409691803	67	110 x 250–270	5100	1, 2, 4	10m 5-wire 2,5mm ² , Wire- end sleeves	3/N/PE ~ 400 (3N) V 50 Hz	36-37	ULG2001V	Floor
UPCRTTC800V9005	4 x 2,0 kW	Black	4260409691810	67	110 x 250–270	5270	1, 2, 4	10m 5-wire 2,5mm ² , Wire- end sleeves	3/N/PE ~ 400 (3N) V 50 Hz	50-51	ULG2001V	Floor
UPCRTTC400V9010	2 x 2,0 kW	White	4260409691827	67	110 x 250–270	4900	1, 2, 4	10m 5-wire 2,5mm ² , Wire- end sleeves	3/N/PE ~ 400 (3N) V 50 Hz	26-28	ULG2001V	Floor
UPCRTTC600V9010	3 x 2,0 kW	White	4260409691834	67	110 x 250–270	5100	1, 2, 4	10m 5-wire 2,5mm ² , Wire- end sleeves	3/N/PE ~ 400 (3N) V 50 Hz	36-37	ULG2001V	Floor
UPCRTTC800V9010	4 x 2,0 kW	White	4260409691841	67	110 x 250–270	5270	1, 2, 4	10m 5-wire 2,5mm ² , Wire- end sleeves	3/N/PE ~ 400 (3N) V 50 Hz	50-51	ULG2001V	Floor



SMART IP24



Code	Wattage	Material Color	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Features	Cable	Connection	Heatable area m ²	Spare tube	Mounting
PCBHS15242	1,5 kW	White	4260051486536	24	63 x 14,5 x 9,5	2500	1, 6	1,90m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	12-13	LGHS1524V	Wall & ceiling
PCBHS20242	2,0 kW	White	4260051486543	24	63 x 14,5 x 9,5	2500	1, 6	1,90m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	LGHS2024	Wall & ceiling
PCBHS30242	2 x 1,5 kW	White	4260051485065	24	111.5 x 14.5 x 9.5	4000	1, 6	1,90m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	24-26	LGHS1524V	Wall & ceiling
PCBHS40242	2 x 2,0 kW	White	4260051485089	24	111.5 x 14.5 x 9.5	4000	1, 6	0,65m 5-wire 2,5mm ² , Wire- end sleeves	2/N/PE ~ 230 V 50 Hz	28-30	LGHS2024	Wall & ceiling

PCBHS60242	3 x 2,0 kW	White	4260051485102	24	151.5 x 14.5 x 9.5	6000	1, 6	0,65m 5-wire 2,5mm ² , Wire- end sleeves	3/N/PE ~ 400 V 50 Hz	36-37	LGHS2024	Wall & ceiling
------------	------------	-------	---------------	----	--------------------	------	------	---	----------------------------	-------	----------	-------------------

The following accessories are necessary for a full functioning system:

Please contact our customer service in this regard!



PERFECTCLIME® Add on




Pump







Code	Wattage	Description	EAN	Mounting
PCE05	70 Bar	0,5 l/m	4260051482347	Floor
PCE1	70 Bar	0,9 l/m	4260051482354	Floor

Coupling



	Code	Description	EAN	Mounting
	PCKT	T-Coupling	4260051483245	Heater and pipeline
	PCKL	L-Coupling	4260051483252	Heater and pipeline



	PCKS	Straight Coupling	4260051483856	Pipeline
	PCKE	End-Coupling	4260051483269	Heater and pipeline
	PCKG	Angle Coupling	4260051483276	Heater and pipeline

Pipeline





	Code	Material/ Description	EAN	Mounting
	PCPS25	Polyamid Pipeline 6,35mm, 25m Black	4260051483290	Heater and pipeline
	PCPG7	Polyamid Gerte 6,35mm, 75cm Black	4260051483313	Heater and pipeline
	PCPC	Polyamid Cutter	4260051483320	Pipeline
	PCPB	Polyamid pipe mounting	4260051483337	Heater and pipeline





Filter

	Code	Description	EAN	Mounting
	PCFKUEU	Filter clause chalk	4260051483344	Pump
	PCFS	Particle filter	4260051483351	Pump

	PCFUV4	UV-Filter, 480l/h	4260051482880	Pump
	PCFUV5	UV-Filter, 500l/h	4260051482897	Pump

Nozzle (Spare)

	Code	Description	EAN	Mounting
	PCN15	Nozzle 0,15mm l/m / US Gpm 56 Bar: 0,041 / 0.011 70 Bar: 0,046 / 0.0095 84 Bar: 0,051 / 0.012	4260051483207	Heater
	PCN20	Nozzle 0,20mm l/m / US Gpm 56 Bar: 0,080 / 0.021 70 Bar: 0,089 / 0.024 84 Bar: 0,098 / 0.026	4260051483214	Heater
	PCN30	Nozzle 0,30mm l/m / US Gpm 56 Bar: 0,130 / 0.034 70 Bar: 0,145 / 0.038 84 Bar: 0,159 / 0.042	4260051483221	Heater
	PCN40	Nozzle 0,40mm l/m / US Gpm 56 Bar: 0,159 / 0.047 70 Bar: 0,178 / 0.047 84 Bar: 0,195 / 0.052	4260051483238	Heater

AUSSTATTUNG: 1 = PERFECTCLIME 2 = ULTRA LOW GLARE  (100% Wärme bei 80% weniger Licht) 3 = NO GLARE  (100% Lichtbeduktion) 4 = Wasserdicht  5 = Licht  6 = LOW GLARE 