

# Datasheet

## SMART TOWER BLUETOOTH IP24



Code	Wattage	Material/Color	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Feature	Cable	Connection	Heatable are in m <sup>2</sup>	Spare tube	Mounting
BTBHS2024	2,0 kW	White	4260409693135	24	48 x 14,5 x 9,5	2500	6	1,90m 3-weire 1,5 mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	LGHS2024	Wall and ceiling
BTBHS2024-1	2,0 kW	Black	4260409693142	24	48 x 14,5 x 9,5	2500	6	1,90m 3-weire 1,5 mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	LGHS2024	Wall and ceiling
BTBHS2024-3	2,0 kW	Silver	4260409693159	24	48 x 14,5 x 9,5	2500	6	1,90m 3-weire 1,5 mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	LGHS2024	Wall and ceiling

**Mounting:** Vertical and horizontal, Face Down possible, 45° mounting angle

**AUSSTATTUNG:** 1 = PERFECTCLIME | 2 = ULTRA LOW GLARE (100% Wärme bei 80% weniger Licht) | 3 = NO GLARE (100% Lichtreduktion) | 4 = Wasserdicht | 5 = Licht | 6 = LOW GLARE