

Datasheet

SMART IP24



Code	Wattage	Material Color	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Feature	Cable	Connection	Heatable area in m ²	Spare tube	Mounting
BHS1524	1,5 kW	White	4260051489568	24	48 x 14,5 x 9,5	2500	6	1,90m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	12-13	LGHS1524V	Wall and ceiling
BHS1524-3	1,5 kW	Silver	4260051489551	24	48 x 14,5 x 9,5	2500	6	1,90m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	12-13	LGHS1524V	Wall and ceiling
BHS2024	2,0 kW	White	4260051489575	24	55,5 x 14,5 x 9,5	2500	6	1,90m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	LGHS2024	Wall and ceiling
BHS2024-3	2,0 kW	Silver	4260051489582	24	48 x 14,5 x 9,5	2500	6	1,90m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	LGHS2024	Wall and ceiling
BHS2024-1	2,0 kW	Black	4260051480053	24	48 x 14,5 x 9,5	2500	6	1,90m 3-wire 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	LGHS2024	Wall and ceiling

Mounting: Vertical and horizontal, Face Down possible, 45° mounting angle

AUSSTATTUNG:

- 1 = PERFECTCLIME
- 2 = ULTRA LOW GLARE (100% Wärme bei 80% weniger Licht)
- 3 = NO GLARE (100% Lichtreduktion)
- 4 = Wasserdicht
- 5 = Licht
- 6 = LOW GLARE