

# Datasheet

## SMART MULTI BLUETOOTH IP24



Code	Wattage	Material/Color	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Feature	Cable	Connection	Heatable area in m <sup>2</sup>	Spare tube	Mounting
BTBHS3024	2 x 1,5 kW	White	4260409694064	24	89,5 x 14,5 x 9,5	4000	6	1,90m 3-wire 1,5mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230 V 50 Hz	24-26	LGHS1524V	Wall and ceiling
BTBHS3024-3	2 x 1,5 kW	Silver	4260409694088	24	89,5 x 14,5 x 9,5	4000	6	1,90m 3-wire 1,5mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230 V 50 Hz	24-26	LGHS1524V	Wall and ceiling
BTBHS3024-1	2 x 1,5 kW	Black	4260409694071	24	89,5 x 14,5 x 9,5	4000	6	1,90m 3-wire 1,5mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230 V 50 Hz	24-26	LGHS1524V	Wall and ceiling

**Mounting:** Vertical and horizontal, Face Down possible, 45° mounting angle

**AUSSTATTUNG:**

- 1 = PERFECTCLIME
- 2 = ULTRA LOW GLARE (100% Wärme bei 80% weniger Licht)
- 3 = NO GLARE (100% Lichtreduktion)
- 4 = Wasserdicht
- 5 = Licht
- 6 = LOW GLARE