

Datasheet

SMART Multi IP24



Code	Wattage	Material/ Color	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Feature	Cable	Connection	Heatable area in m ²	Spare tube	Mounting
BHS3024	2 x 1,5 kW	White	4260051487243	24	89,5 x 14,5 x 9,5	4000	6	1,90m 3-weire 1,5mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	24-26	LGHS1524V	Wall and ceiling
BHS4024	2 x 2,0 kW	White	4260051487267	24	89,5 x 14,5 x 9,5	4000	6	0,65m 5-weire 2,5mm ² , Wire-end sleeves	2/N/PE ~ 230 V 50 Hz	28-30	LGHS2024	Wall and ceiling
BHS6024	3 x 2,0 kW	White	4260051487281	24	129 x 14,5 x 9,5	6000	6	0,65m 5-weire 2,5mm ² , Wire-end sleeves	3/N/PE ~ 400 (3N) V 50 Hz	42-44	LGHS2024	Wall and ceiling

Montage: Vertical and horizontal, Face Down possible, 45° mounting angle

AUSSTATTUNG:

- 1 = PERFECTCLIME
- 2 = ULTRA LOW GLARE (100% Wärme bei 80% weniger Licht)
- 3 = NO GLARE (100% Lichtreduktion)
- 4 = Wasserdicht
- 5 = Licht
- 6 = LOW GLARE

Burda Worldwide Technologies GmbH – Rudolf-Diesel-Straße 18 – 65760 Eschborn – T: +49 6173 324240 – F: +49 6173 3242424 – info@burdawtg.de – www.burdawtg.de