

# Datasheet

## SMART S IP24



Code	Wattage	Material Color	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Feature	Cable	Connection	Heatable area in m <sup>2</sup>	Spare tube	Mounting
BHSS1524	1,5 kW	White	4260051489568	24	48 x 14,5 x 9,5	2500	6	1,90m 3-wire 1,5 mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230 V 50 Hz	12-13	LGHS1524V	Wall and ceiling
BHSS1524-3	1,5 kW	Silver	4260051489568	24	48 x 14,5 x 9,5	2500	6	1,90m 3-wire 1,5 mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230 V 50 Hz	12-13	LGHS1524V	Wall and ceiling
BHSS1524-1	1,5 kW	Black	4260051489568	24	48 x 14,5 x 9,5	2500	6	1,90m 3-wire 1,5 mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	LGHS1524V	Wall and ceiling
BHSS2024	2,0 kW	White	4260051489568	24	55,5 x 14,5 x 9,5	2500	6	1,90m 3-wire 1,5 mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	LGHS2024	Wall and ceiling
BHSS2024-3	2,0 kW	Silver	4260051489568	24	48 x 14,5 x 9,5	2500	6	1,90m 3-wire 1,5 mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	LGHS2024	Wall and ceiling
BHSS2024-1	2,0 kW	Black	4260051489568	24	48 x 14,5 x 9,5	2500	6	1,90m 3-wire 1,5 mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	LGHS2024	Wall and ceiling

**AUSSTATTUNG:**

- 1 = PERFECTCLIME
- 2 = ULTRA LOW GLARE (100% Wärme bei 80% weniger Licht)
- 3 = NO GLARE (100% Lichtreduktion)
- 4 = Wasserdicht
- 5 = Licht
- 6 = LOW GLARE

Burda Worldwide Technologies GmbH – Rudolf-Diesel-Straße 18 – 65760 Eschborn – T: +49 6173 324240 – F: +49 6173 3242424 – [info@burdawtg.de](mailto:info@burdawtg.de) – [www.burdawtg.de](http://www.burdawtg.de)