

Datasheet

SMART TOWER BLUETOOTH IP24



Code	Wattage	Material Color	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Feature	Cable	Connection	Heatable area in m ²	Spare tube	Mounting
BTBHST3024-1	2 x 1,5kW	Black	4260409694026	IP24	29 x 126 x 32	7300	6	1,90m 3-wire 1,5mm ² , Schuko plug	1/N/PE ~ 230V 50Hz	24-26	LGHS1524V	Boden
BTBHST3024-2	2 x 1,5kW	White	4260409694002	IP24	29 x 126 x 32	7300	6	1,90m 3-wire 1,5mm ² , Schuko plug	1/N/PE ~ 230V 50Hz	24-26	LGHS1524V	Boden
BTBHS3024-3	2 x 1,5kW	Silver	4260409694019	IP24	29 x 126 x 32	7300	6	1,90m 3-wire 1,5mm ² , Schuko plug	1/N/PE ~ 230V 50Hz	24-26	LGHS1524V	Boden

AUSSTATTUNG: 1 = PERFECTCLIME | 2 = ULTRA LOW GLARE (100% Wärme bei 80% weniger Licht) | 3 = NO GLARE (100% Lichtreduktion) | 4 = Wasserdicht | 5 = Licht | 6 = LOW GLARE