

Datasheet

TERM2000 BLUETOOTH IP67



Code	Wattage	Material Color	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Cable	Features	Heatable area in m ²	Mounting	Spare tube	Control
BTURCAC200V9010	2,0kW	White	4260409692442	IP67	71 x 9,5 x 12,5	2500	1,9m 3-wire 1,5 mm ² , Schuko plug/ 1/N/PE ~ 230 V 50 Hz	2,4	14-16	Wall and ceiling	ULG2001V	1.Switch 2. Remote Control 3. BURDA APP
BTURCAC200V7016	2,0kW	Anthracite	4260409692459	IP67	71 x 9,5 x 12,5	2500	1,9m 3-wire 1,5 mm ² , Schuko plug/ 1/N/PE ~ 230 V 50 Hz	2,4	14-16	Wall and ceiling	ULG2001V	1. Switch 2. Remote Control 3. BURDA APP
BTURCAC200V9005	2,0kW	Black	4260409692435	IP67	71 x 9,5 x 12,5	2500	1,9m 3-wire 1,5 mm ² , Schuko plug/ 1/N/PE ~ 230 V 50 Hz	2,4	14-16	Wall and ceiling	ULG2001V	1.Switch 2. Remote Control 3. BURDA APP

AUSSTATTUNG: 1 = PERFECTCLIME | 2 = ULTRA LOW GLARE (100% Wärme bei 80% weniger Licht) | 3 = NO GLARE (100% Lichtreduktion) | 4 = Wasserdicht | 5 = Licht | 6 = LOW GLARE