

Datasheet

TERM2000 COLOR SHORT IP44



Code	Wattage	Material Color	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Features	Cable	Connection	Heatable area in m ²	Spare tube	Mounting
URCACS01044V9010	1,0 kW	White	4260051488592	IP44	46,4 x 9,5 x12,5	2100	2	1,90m 3-wire 1,5mm ² , Schuko plug	1/N/PE ~ 230V 50Hz	9-11	ULGS1024V	Wall and ceiling
URCACS01544V9010	1,5 kW	White	4260051488370	IP44	46,4 x 9,5 x12,5	2100	2	1,90m 3-wire 1,5mm ² , Schuko plug	1/N/PE ~ 230V 50Hz	12-13	ULGS1524V	Wall and ceiling
URCACS01044V9005	1,0 kW	Black	4260051488608	IP44	46,4 x 9,5 x12,5	2100	2	1,90m 3-wire 1,5mm ² , Schuko plug	1/N/PE ~ 230V 50Hz	9-11	ULGS1024V	Wall and ceiling
URCACS01544V9005	1,5 kW	Black	4260051488394	IP44	46,4 x 9,5 x12,5	2100	2	1,90m 3-wire 1,5mm ² , Schuko plug	1/N/PE ~ 230V 50Hz	12-13	ULGS1524V	Wall and ceiling
URCACS01044V7016	1,0 kW	Anthracite	4260051488615	IP44	46,4 x 9,5 x12,5	2100	2	1,90m 3-wire 1,5mm ² , Schuko plug	1/N/PE ~ 230V 50Hz	9-11	ULGS1024V	Wall and ceiling
URCACS01544V7016	1,5 kW	Anthracite	4260051488424	IP44	46,4 x 9,5 x12,5	2100	2	1,90m 3-wire 1,5mm ² , Schuko plug	1/N/PE ~ 230V 50Hz	12-13	ULGS1524V	Wall and ceiling

Montage: Vertical and horizontal, No Face Down, 45° angle

AUSSTATTUNG:

- 1 = PERFECTCLIME**
- 2 = ULTRA LOW GLARE** 
(100% Wärme bei 80% weniger Licht)
- 3 = NO GLARE** 
(100% Lichtreduktion)
- 4 = Wasserdicht** 
- 5 = Licht** 
- 6 = LOW GLARE** 