

# Datasheet

## TERM2000 IP44



Code	Wattage	Material Color	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Feature	Cable	Connection	Heatable area in m <sup>2</sup>	Spare tube	Mounting
URCA01044V	1,0 kW	Alu polished	4260051488653	44	51,5 x 9,5 x 12,5	2300	2	1,90m 3-wire 1,5mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230V 50Hz	9-11	ULGS1024V	Wall and ceiling
URCA01544V	1,5 kW	Alu polished	4260051488509	44	51,5 x 9,5 x 12,5	2300	2	1,90m 3-wire 1,5mm <sup>2</sup> , Schuko plug	1/N/PE ~ 230V 50Hz	12-13	ULGS1524V	Wall and ceiling

**Montage:** Vertical and horizontal, No Face Down, 45° mounting angle

**AUSSTATTUNG:** 1 = PERFECTCLIME | 2 = ULTRA LOW GLARE (100% Wärme bei 80% weniger Licht) | 3 = NO GLARE (100% Lichtreduktion) | 4 = Wasserdicht | 5 = Licht | 6 = LOW GLARE

Burda Worldwide Technologies GmbH – Rudolf-Diesel-Straße 18 – 65760 Eschborn – T: +49 6173 324240 – F: +49 6173 3242424 – [info@burdawtg.de](mailto:info@burdawtg.de) – [www.burdawtg.de](http://www.burdawtg.de)