

# Datasheet

## TERM2000 IP67 Hirschmann



Code	Wattage	Material/Color	EAN	IP	Dimensions BxHxT in cm	Weight (in g)	Features	Cable	Connection	Heatable area in m <sup>2</sup>	Spare tube	Mounting
URCA165VH	1 x 1,65 kW	Alu polished	4260051484181	IP67	61 x 9,5 x 12,5	2500	2, 4	1,90 m 3-wire 1,5 mm <sup>2</sup> , Schuko plug with Hirschmannset	1/N/PE ~ 230 V 50 Hz	13-14	ULG1650V	Wall and ceiling
URCA200VH	1 x 2,0 kW	Alu polished	4260051484198	IP67	61 x 9,5 x 12,5	2500	2, 4	1,90 m 3-wire 1,5 mm <sup>2</sup> , Schuko plug with Hirschmannset	1/N/PE ~ 230 V 50 Hz	14-16	ULG2001V	Wall and ceiling

**AUSSTATTUNG:**

- 1 = PERFECTCLIME
- 2 = ULTRA LOW GLARE  
(100% Wärme bei 80% weniger Licht)
- 3 = NO GLARE  
(100% Lichtreduktion)
- 4 = Wasserdicht
- 5 = Licht
- 6 = LOW GLARE