

# Datasheet

## TERM2000 L&H LED IP65



Code	Wattage	Material/Color	EAN	IP	Dimensions WxHxD in cm	Weight (in g)	Feature	Cable	Connection	Heatable area in m <sup>2</sup>	Spare tube	Mounting
URLH1765	1,65 kW + 7 Watt	Alu polished	4260051484020	IP65	82,5 x 9,5 x 12,5	3350	2,4,5	1,9m 5-wire 1,5mm <sup>2</sup> , Wire-end sleeves	2/N/PE ~ 230 V 50 Hz	13-14	ULG1650V	Wall and ceiling
URLH2165	2,0 kW + 7 Watt	Alu polished	4260051484037	IP65	82,5 x 9,5 x 12,5	3350	2,4,5	1,9m 5-wire 1,5mm <sup>2</sup> , Wire-end sleeves	2/N/PE ~ 230 V 50 Hz	14-16	ULG2001V	Wall and ceiling
URLH1765F	1,65 kW + 7 Watt	Alu polished	4260051484044	IP65	78 x 9,5 x 12,5	3350	2, 4, 5	1,9m 5-wire 1,5mm <sup>2</sup> , Wire-end sleeves	2/N/PE ~ 230 V 50 Hz	13-14	ULG1650V	Wall and ceiling
URLH2165F	2,0 kW + 7 Watt	Alu polished	4260051484051	IP65	78 x 9,5 x 12,5	3350	2, 4, 5	1,9m 5-wire 1,5mm <sup>2</sup> , Wire-end sleeves	2/N/PE ~ 230 V 50 Hz	14-16	ULG2001V	Wall and ceiling

**AUSSTATTUNG:**

- 1 = PERFECTCLIME
- 2 = ULTRA LOW GLARE (100% Wärme bei 80% weniger Licht)
- 3 = NO GLARE (100% Lichtreduktion)
- 4 = Wasserdicht
- 5 = Licht
- 6 = LOW GLARE