

Datenblatt

TIMER SOFTSTART



| Code | Leistung | Material/Farbe | EAN | IP | Abmessungen BxHxT in cm | Gewicht (in g) | Einstellungen | Kabel | Stromanschluss |
|-------|----------|----------------|---------------|------|-------------------------|----------------|-----------------|---|-------------------------|
| TS2-C | 2,0 kW | Weiß | 4260051480107 | IP55 | 9,5 x 13 x 5,5 | 475 | 5 – 60 Sekunden | 1,5m 3-adrig 1,5mm ² PVC; 0,5m 3-adrig 1,5mm ² PVC, Schukostecker | 1/N/PE ~ 230 V 50 Hz |
| TS4 | 4,0 kW | Weiß | 4260051480077 | IP65 | 10 x 12,5 x 7 | 475 | 1 – 40 Minuten | 1,5m 3-adrig 1,5mm ² PVC; 0,5m 3-adrig 1,5mm ² PVC, Schukostecker | 1/N/PE ~ 230 V 50 Hz |
| TS6 | 6,0kW | Weiß | 4260409691254 | IP65 | 13 x 13 x 7 | 475 | 1 – 30 Minuten | 1,5m 3-adrig 1,5mm ² PVC; 0,5m 3-adrig 1,5mm ² PVC, Schukostecker | 1/N/PE ~ 230 V 50 Hz |