

Datasheet

SMART FRAME IP24



Code	Wattage	Material/Color	EAN	IP	Dimensions (WxHxD in cm)	Weight (in g)	Features	Cable	Connection	Heatable area in m ²	Spare tube	Mounting
BHSF1524-2	1,5 kW	White	4260409694842	IP24	60 x 32,5 x 10	3400	6	1,90m 3-adrig 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	12-13	LGHS1524V	Wall horizontal and ceiling face down
BHSF1524-3	1,5 kW	Silver	4260409694859	IP24	60 x 32,5 x 10	3400	6	1,90m 3-adrig 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	12-13	LGHS1524V	Wall horizontal and ceiling face down
BHSF2024-2	2,0 kW	White	4260409694835	IP24	60 x 32,5 x 10	3400	6	1,90m 3-adrig 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	LGHS2024	Wall horizontal and ceiling face down
BHSF2024-3	2,0 kW	Silver	4260409694866	IP24	60 x 32,5 x 10	3400	6	1,90m 3-adrig 1,5 mm ² , Schuko plug	1/N/PE ~ 230 V 50 Hz	14-16	LGHS2024	Wall horizontal and ceiling face down

AUSSTATTUNG:

- 1 = PERFECTCLIME
- 2 = ULTRA LOW GLARE (100% Wärme bei 80% weniger Licht)
- 3 = NO GLARE (100% Lichtreduktion)
- 4 = Wasserdicht
- 5 = Licht
- 6 = LOW GLARE